

AV Series – Vertical Outlet Acetylene Valves

O-Ring Seal Technology for Acetylene Gases

HARRISON

PRECISION VALVE PRODUCTS

Tapered, NGT Threads for Steel Cylinders

All Harrison Valves™ are produced to meet or exceed the highest US and international standards; including ISO 10297 and CGA V-9. Harrison Valves™ are rigorously tested through a robust quality assurance system, and Harrison Valves™ maintains carefully monitored manufacturing processes to ensure that all Harrison Valves™ meet or exceed design and performance specifications.

KEY FEATURES:

- Handwheel design to replace old "Linde" style Acetylene cylinder valves and vertical outlets.
- No wrench needed for operation.
- O-ring seal technology provides superior leak integrity.
- Easy operation under all pressures.
- 100% leak testing on entire production.
- Meets and exceeds CGA V9 and ISO 10297.
- All valves bagged for cleanliness no matter the gas service intended.
- Lower plugs are designed specific for the gas service intended.

SPECIFICATIONS:

All VA510 series valves are supplied without a safety device. All AV510 series valves are to be used in manifolds or in conjunction with a fusible metal CG3 plug when utilized in a large acetylene cylinder.



Part Number	CGA Designation	Gas Service	Inlet Thread Size	Safety Device	Service/Safety
AV510-6-0	CGA510	Acetylene	3/4" NGT	No safety Device	No Safety Device

Fusible Plugs For Acetylene

KEY FEATURES:

- Produced from high quality brass and steel alloy rod.
- Meticulously controlled fusible alloy assures accurate and consistent melt temperatures.
- Fusible alloy is cast into plug body to ensure an extremely strong bond between alloy and plug body.
- Fusible plug stamped with fusible metal yield temperature.



Part Number	Thread Size	Fuse Metal
SFP-212-1	1/8" NPT	212°F
BFB-212-1	1/8" NPT	212°F
BFB-212-2	1/4" NPT	212°F

HARRISON

www.HarrisonValve.com